

MOBILE MEAL DELIVERY TRAY CART

- STAINLESS STEEL
- LOW PROFILE
- SINGLE COMPARTMENT

- PASS-THROUGH DESIGN
- DOUBLE DOORS
- VARIABLE SPACING

MODEL NO: 1001-XXXX-XX-XX-DD

APPLICATION:

- Enclosed meal delivery and return

SPECIFICATIONS:

- Stainless steel; Type 304
- “Heliarc” and spot-welded construction
- Single compartment, pass through design
- Low profile design
- Solid top and base
- Enclosed 2 sides with vented side panels
- Front and back to have 270 degree fold-back stainless steel doors with paddle latch closure
- Hold open catches affixed at top of each side of unit
- Drain hole centred in sanitary edge base
- Up to 8 sets of fixed welded angle slides with dimples on each end to assist in securing trays
- 2 trays per slide
- Up to 16 tray total capacity
- 4”, 4.5”, 5”, & 6” slide tray spacing available
- Tray size to be determined
- Bottom slide is 1 3/16” up from base
- 4 > 1” tubing style stainless steel push handles with rubber grips at top of unit (model cannot accommodate side push handles)
- Flush style wrap around bumper wrapped over stainless steel core for strength and durability
- 4 > 5” swivel casters with 2 side brakes
- Maximum height of unit cannot exceed 50” with handles

OPTIONAL FEATURES: [1]

- INS - Insulated model
- Turned up slide edges for tray transport security
- 1” stainless steel ergonomic handle with rubber grips at one edge of top in place of railing
- Drain plug assembly for drain hole
- Menu card pocket; stainless steel
- Front “C” catch for additional security on doors while in transport
- Drop down locking catch for padlock closure
- Rigid casters opposite handle end
- Balloon style casters or casters for outside transportation
- Retractable or spring loaded drop-down tow hitch & pin assembly

Shown with optional ergonomic handle and padlock closure



Shown with optional balloon style casters

Contact Factory with your specific tray size, capacity, and spacing requirements for dimensions.

© Copyright 2015 Hatch Industries Limited

CANADA/USA TOLL FREE: 1-800-387-6969 FAX: 1-519-822-8365 www.hatchindustries.com